

CX308ST



- Short throw projector
- Built-in 10W speaker
- 28dB low noise
- Bright 3600 lumens
- Versatile connectivity

Specification

| | | | |
|-------------------------------|--|----------------------------|---|
| Display Technology | Texas Instrument DMD, 0.55" XGA DMD | Native Resolution | XGA(1024 x 768) |
| Brightness / Contrast Ratio | 3600 ANSI Lumens / 22,000:1 | Display Colors | 1.07 billion |
| Projection Lens | F=2.7 ; f = 7.15mm ; Fixed Lens | Image Size | 31.9" to 303.09" |
| Projection Distance | 0.4~3.8m | Throw Ratio | 0.62 |
| Digital Keystone Correction | ± 20° Vertical | Aspect Ratio | 4:3 |
| Light Source Power | 203W | Noise | 28dB low noise |
| Lamp Life | 6000/10000/10000/15000 (Normal/ECO/Dynamic/ECO+ Mode) | Speaker | 10W |
| Scan Rate | Horizontal scan rate: 15.375 ~ 91.146 KHz; Vertical scan rate: 50 ~ 85 Hz | Input / Output Connections | HDMIx1, VGA-in x 1 , VGA-out x1,USB Power x1 Audio-in x1, Audio-out x1,RS232 x1 |
| Dimensions(W x D x H)/ Weight | 31.6x24.4x9.8(cm) / 2.9(kg) | Power Supply | AC 100 ~240V (50~60Hz) |



Optoma Corporation
 12F., No.213, Sec. 3, Beixin Rd.,
 Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
 Tel: +886 2 8911 8600 Fax: +886 2 8911 6550
<http://www.optoma.com.tw>